



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C12Q 1/68, 1/70, C12P 19/34, C03B 37/15, G01N 21/01, 21/29, 27/00, 27/30, 21/27, 21/31, 21/76, 21/25	A1	(11) International Publication Number: WO 97/27326 (43) International Publication Date: 31 July 1997 (31.07.97)
(21) International Application Number: PCT/US97/01052 (22) International Filing Date: 24 January 1997 (24.01.97) (30) Priority Data: 08/592,779 26 January 1996 (26.01.96) US (71) Applicants: THE REGENTS OF THE UNIVERSITY OF CALIFORNIA [US/US]; 22nd floor, 300 Lakeside Drive, Oakland, CA 94612 (US). MEDICAL RESEARCH COUNCIL [GB/GB]; 20 Park Crescent, London W1N 4AL (GB). (72) Inventors: PINKEL, Daniel; 31 Manzanita Court, Walnut Creek, CA 94595 (US). SEGRAVES, Richard; 38061 Parkmont Drive, Fremont, CA 94536 (US). ZHAI, Ye; 628 Waverly Street #A, Palo Alto, CA 94301 (US). ALBERTSON, Donna, G.; 3302 Bert Lane, Lafayette, CA 94549 (US). (74) Agents: BASTIAN, Kevin, L. et al.; Townsend and Townsend and Crew L.L.P., Two Embarcadero Center, 8th floor, San Francisco, CA 94111 (US).		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: HIGH DENSITY ARRAY FABRICATION AND READOUT METHOD FOR A FIBER OPTIC BIOSENSOR		
(57) Abstract <p>The invention relates to the fabrication and use of biosensors comprising a plurality of optical fibers each fiber having attached to its "sensor end" biological "binding partners" (molecules that specifically bind other molecules to form a binding complex such as antibody-antigen, lectin-carbohydrate, nucleic acid-nucleic acid, biotin-avidin, etc.). The biosensor preferably bears two or more different species of biological binding partner. The sensor is fabricated by providing a plurality of groups of optical fibers. Each group is treated as a batch to attach a different species of biological binding partner to the sensor ends of the fibers comprising that bundle. Each fiber, or group of fibers within a bundle, may be uniquely identified so that the fibers, or group of fibers, when later combined in an array of different fibers, can be discretely addressed. Fibers or groups of fibers are then selected and discretely separated from different bundles. The discretely separated fibers are then combined at their sensor ends to produce a high density sensor array of fibers capable of assaying simultaneously the binding of components of a test sample to the various binding partners on the different fibers of the sensor array. The transmission ends of the optical fibers are then discretely addressed to detectors - such as a multiplicity of optical sensors. An optical signal, produced by binding of the binding partner to its substrate to form a binding complex, is conducted through the optical fiber or group of fibers to a detector for each discrete test. By examining the addressed transmission ends of fibers, or groups of fibers, the addressed transmission ends can transmit unique patterns assisting in rapid sample identification by the sensor.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

5 **HIGH DENSITY ARRAY FABRICATION AND READOUT**
 METHOD FOR A FIBER OPTIC BIOSENSOR

 This invention was made in part with government support under Grant (or
Contract) No. CA45919 awarded by the National Institutes of Health. The government
has certain rights in this invention.

10

 This invention relates to the fabrication and use of biosensors comprising
biological "binding partners" (molecules that specifically bind other molecules to form a
binding complex such as antibody-antigen, lectin-carbohydrate, nucleic acid-nucleic acid,
biotin-avidin, *etc.*) linked to optical fibers. The invention provides improved methods
for attachment of various biomolecules to solid surfaces, particularly optical fibers.

15

Batches of optical fibers are mass processed with the same species of binding partner,
singulated from their particular batch, and regrouped with like optical fibers from other
batches having other species of binding partners.

20

 This invention was made with the Government support under Grant No.
CA 45919, awarded by the National Institute of Health and under Grant No. DE-AC03-
76SF0098, awarded by the Department of Energy. The Government has certain rights in
this invention.

BACKGROUND OF THE INVENTION

25

Biosensors are sensors that detect chemical species with high selectivity on
the basis of molecular recognition rather than the physical properties of analytes. *See,*
e.g., Advances in Biosensors, A.P.F. Turner, Ed. JAI Press, London, (1991). Many
types of biosensing devices have been developed in recent years, including enzyme
electrodes, optical immunosensors, ligand-receptor amperometers, and evanescent-wave
probes. Updike and Hicks, *Nature*, 214: 986 (1967), Abdel-Latif *et al.*, *Anal. Lett.*, 21:
943 (111988); Giaever, *J. Immunol.*, 110: 1424 (1973); Sugao *et al.* *Anal. Chem.*, 65:
363 (1993), Rogers *et al.* *Anal. Biochem.*, 182: 353 (1989).

30

Biosensors comprising a biological "binding molecule" attached to an optical fiber are well known in the prior art, most typically as evanescent wave detectors (see, for example, U.S. Patent 4,447,546 to Hirschfeld and U.S. Patents 4,582,809 and 4,909,990 to Block *et al.*). In order to maximize sensitivity and selectivity such biosensors typically utilize a single species of biological binding molecule affixed to the face of the sensor.

Such "single-species" biosensors are limited in that they have no inherent means to correct or calibrate for non-specific binding. Thus, they must be calibrated against an external standard. In addition, they are limited to the detection of a single analyte.

Biosensors comprising two or more species of biological binding partners overcome these limitations. A "multi-species" biosensor in principle permits simultaneous detection of as many different types of analytes as there are species of biological binding partner incorporated into the sensor. In addition, comparison of the amounts of a single analyte binding to multiple species of binding partner provides a measure of non-specific binding and thus acts as an intrinsic control for measurement variability introduced by non-specific binding.

In addition, the inclusion of fibers bearing biological binding partners specific for various analytes known to create a background signal in a particular assay provides a means for simultaneously measuring and subtracting out the background signal. The provision of a multiplicity of fibers bearing different species of binding partner allows the detection of a multiplicity of moieties contributing to a background, or other, signal and the dissecting out of the contribution of each moiety to that signal.

To be most useful, a multi-species biosensor requires that the sensor provide a separate signal characterizing binding of analytes to each of the various species of binding partner comprising the probe. Thus each species of binding partner must be individually "addressed".

In addition, a "sensor face" (the surface bearing the biological binding partners) that has a relatively small surface area will facilitate measurement of small sample volumes as less sample material will be required to fully immerse the sensor face. A small surface area detector will also prove advantageous for use in *in vitro* measurements. Preparation of a detector bearing a large number of different biological

binding partners that occupies a small area may be viewed as the preparation of a high density array of biological binding partners.

The creation of high density arrays of biological binding partners where each species of binding partner is uniquely addressed presents formidable fabrication problems. One of the most successful approaches, to date, is the large scale photolithographic solid phase synthesis pioneered by Affymax Inc. (*see, e.g., Fodor et al. Science* 251: 767-773 (1991) and U.S. Patent No. 5,143,854). In this approach arrays of peptides or nucleic acids are chemically synthesized on a solid support. Different molecules are simultaneously synthesized at different predetermined locations on the substrate by the use of a photolithographic process that selectively removes photolabile protecting groups on the growing molecules in particular selected locations of the substrate. The resulting array of molecules is "spatially addressed". In other words the identity of each biological molecule is determined by its location on the substrate.

The photolithographic approach, however, is limited to molecules that can be chemically synthesized. Thus, it is typically restricted to peptides shorter than about 50 amino acids and nucleic acids shorter than about 150 base pairs. In addition, the photolithographic approach typically produces such arrays on a planar substrate (*e.g.* a glass slide) and provides no intrinsic mechanism by which a signal produced by the binding of a particular biological binding partner may be transmitted.

U.S. Patent No. 5,250,264 to Walt *et al.* discloses a sensor comprising a fiber optic array using a "plurality of different dyes immobilized at individual spatial positions on the surface of the sensor." Each dye is capable of responding to a different analyte (*e.g., pH, O₂, CO₂, etc.*) and the sensor as a whole is capable of providing simultaneous measurements of multiple analytes.

Although the sensor disclosed by Walt *et al.* is not a biosensor, the reference describes a means of fabricating a sensor bearing a plurality of uniquely addressed "detection moieties". In Walt *et al.* optical fibers are first assembled to form a bundle. Transmission ends of a fiber or group of fibers of are then specifically illuminated. Each illuminated fiber transmits the light to its respective sensor end where the light "photopolymerizes" a sensor dye mixture causing the dye to bind to the sensor end. This process is repeated with different fibers for different photopolymerized dyes. This repetition continues until a sensor array is constructed.

This approach suffers from the limitations that it requires photopolymerizable sensor dyes and thus is limited in the number of different species per probe by the number of different dye type. In addition, this reference provides no means for attaching uniquely addressed biological molecules (*e.g.* peptides, nucleic acids, antibodies) to the sensor. Thus Walt *et al.* provide no means for the fabrication of biosensors.

SUMMARY OF THE INVENTION

The present invention provides a novel means for fabricating biosensors comprising a plurality of biological "binding partners" (molecules that specifically bind other molecules to form a binding complex such as antibody-antigen, lectin-carbohydrate, nucleic acid-nucleic acid, biotin-avidin, *etc.*) linked to optical fibers. In particular the method provides a means of preparing a high density array of biological binding partners where each species of binding partner is uniquely addressed. In contrast to certain methods in the prior art the biological binding partners utilized in the present invention are not limited to chemically synthesized oligonucleotides or peptides, but rather include nucleic acids, antibodies, proteins, lectins and other binding partners derived from cells, tissues or organisms in their native state or otherwise modified through the methods of recombinant DNA technology.

The invention also provides improved methods for the attachment of various biomolecules (*e.g.*, nucleic acids) to solid surfaces. The methods involve the use of a matrix solution comprising the biomolecule of interest and an organic or inorganic matrix polymer. Typically, the matrix solution is monophasic solution comprising both the matrix polymer (*e.g.*, nitrocellulose) in an appropriate solvent (*e.g.*, DMSO) and an aqueous solution of the nucleic acid or other biomolecule. The matrix solutions of the invention can be used for attachment of nucleic acids and other biopolymers to any solid surface commonly used as a solid surface in nucleic acid hybridization, immunoassays and the like. Exemplary solid surfaces include glass (*e.g.*, optic fibers, slides, and beads), plastics, quartz, and the like.

In particular, the biosensors of the present invention comprise a multiplicity of optical fibers bundled together to form an optical fiber array. The sensor end of each optical fiber or group of optical fibers comprising the optical fiber array bear

a particular species of biological binding partner. Optical signals produced by binding of an analyte to a biological binding partner are conducted along the respective optical fibers to a transmission end which may be attached to a detector. Detection of the signal from the fibers corresponding to each species of biological binding partner provides a simultaneous measurement of the binding of a multiplicity of analytes.

The present invention provides a method of fabrication of fiber optic biosensors. The method involves providing a multiplicity of optical fibers which are grouped into a plurality of separate fiber groups or batches. Each fiber has a sensor end and a transmission end and the fibers in each group are oriented so that the sensor ends are commonly aligned. Each group of fibers is then treated to attach a single species of biological binding partner to the sensor ends of the constituent fibers. Alternatively, a multiplicity of species of biological binding partner may be attached to each group as long as the multiplicity of species of biological binding partners attached to one fiber group is different than the multiplicity of species attached to the other fiber groups.

Fibers or groups of fibers are then selected and discretely separated from their respective batches. One or more of the discretely separated fibers from each group are then recombined at their sensor ends with other fibers from other batches to produce an optical fiber array. The sensor ends may be arranged in a substantially planar orientation or may be tiered to form a tiered sensor face. The optical fiber array contains fibers capable of assaying simultaneously the binding of components of a test sample to the various binding partners on the different fibers of optical fiber array.

The batch identity of each fiber is maintained during the bundling process, preferably at or adjacent to the transmission end of the fibers. These transmission ends are then discretely addressed to detectors - such as a multiplicity of optical sensors. The location and spatial array of the transmission ends corresponding to particular biological binding partners are distinct from one another and known.

Thus, the invention provides for the fabrication of a high density array of biological binding partners in which each binding partner is uniquely addressed. An optical signal, produced by binding of the binding partner to its substrate to form a binding complex, is conducted through the optical fiber or group of fibers to a detector for each discrete test. Thus, binding of a molecule to a particular biological binding partner is specifically detectable. By examining the addressed transmission ends of

fibers, or groups of fibers, the addressed transmission ends can transmit unique patterns assisting in rapid sample identification of analytes by the sensor.

In one embodiment, the fiber optics might bear nucleic acid binding partners to which nucleic acids in the test sample might hybridize. As used herein, the terms "nucleic acid" or "nucleic acid molecule" refer to a deoxyribonucleotide or ribonucleotide polymer in either single- or double-stranded form, and unless otherwise limited, would encompass known analogs of natural nucleotides that can function in a similar manner as naturally occurring nucleotides.

In one particularly preferred embodiment, the biosensor comprises a plurality of fibers, each fiber including an sensor end and a transmission end, the sensor end of at least one first fiber having attached a first biological binding partner and the sensor end of at least one second fiber having attached a second biological binding partner, a transmission array having first and second positions addressing the transmission ends of the first and second fibers, means for addressing the transmission ends of the first and second fibers to the transmission array, optical interrogation means adjacent the transmission ends for examining the comparative attachment of analytes at the sensor ends of the fibers. The sensor ends of the first and second fibers may be arranged to form a tiered sensor face. The first and second binding partners may be nucleic acids, for example, DNA and cDNA. The nucleic acids may be mapped to specific regions on one or more human chromosomes or may be expressed sequences such as cDNA or mRNA. In a particularly preferred embodiment, the target nucleic acids are about 1,000 to 1,000,000 nucleotides in complexity.

Nucleic acid bearing arrays are particularly useful in Comparative Genomic Hybridization (CGH) assays to detect chromosomal abnormalities; in particular increases or decreases in copy number of particular chromosomal regions. In one example of this approach, a first collection of (probe) nucleic acids is labeled with a first label, while a second collection of (probe) nucleic acids is labeled with a second label. A biosensor, as described above, is one in which the biological binding partners are target nucleic acids. (As used herein the term "target nucleic acids" typically refers to nucleic acids attached to the optical fibers comprising the fiber optic array, while "probe nucleic acids" are those nucleic acids free in solution that hybridize with the target nucleic acids.) The ratio of hybridization of the nucleic acids is determined by the ratio

of the two (first and second) labels binding to each fiber in the array. Where there are chromosomal deletions or multiplications, differences in the ratio of the signals from the two labels will be detected. Identification of the specific optical fibers in the array giving rise to these ratios will indicate the nucleic acid sequence the probe bears and thus the nucleic acid sequence that is altered.

The target nucleic acids (the nucleic acids attached to the optical fibers) may include DNA and cDNA and may be mapped to specific regions in human chromosomes. In addition, the target nucleic acids are preferably about 1,000 to 1,000,000 nucleotides in complexity. The complexity of the sequence complementary to the target nucleic acid is preferably less than 1% of the total complexity of the sequences in the sample.

The first and second labels are preferably fluorescent labels. In a particularly preferred embodiment, the first probe nucleic acids comprise mRNA or cDNA from a test cell and the second probe nucleic acids comprise mRNA or cDNA from a reference cell. In another preferred embodiment, the first probe nucleic acids are from a test genome and the second probe nucleic acids are from a reference genome. The test genome may comprise nucleic acids from fetal tissue or from a tumor.

According to one aspect of the invention, arrays of optical fibers are disclosed where the interrogating end of each fiber in the array comprises a multiplicity of biological "binding partners." Each binding partner is attached to one or more optical fibers specifically addressed or identified at the transmitting end as being connected to the particular binding partner. With the transmission ends properly addressed and interrogated, measurement occurs.

In one specific embodiment, arrays of optical fibers bearing nucleic acid molecules are disclosed. These optical fibers at their interrogating ends have specific nucleic acids such as nucleic acids having a certain minimum length (*e.g.* 400 bp), or being derived from particular libraries (*e.g.* evenly spaced along a particular chromosome or representing a particular gene).

It is an advantage of the disclosed apparatus and process that the constructed array can be tailored to rapid screening of extensive arrays of biological binding partners. Using already identified information, arrays can be assembled which can simultaneously and rapidly survey samples nucleic acid variations across entire
5 genomes. For example, a fiber optic sensor bearing 30,000 target nucleic acids, each containing 100kb of genomic DNA could give complete coverage of the human genome.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration showing a group of fibers with the
10 sensor ends bound together for joint treatment to attach a binding partner and the transmission ends discretely marked to enable the fibers of the illustrated group to be distinguished from fibers of similar groups when subsequent separation of the fibers later occurs from the group.

Figure 2 illustrates a plurality of differing batches of treatment solution
15 with the sensor ends of the group of fibers of Figure 1 being immersed for treatment in one of the fiber batches;

Figure 3 illustrates differing groups of previously treated fibers lying side-by-side with fibers being singulated from each group for gathering into a common high density array.

Figure 4 illustrates an assembled high density array at the sensor and
20 transmitting ends only with disposition of the sensor ends in a tiered disposition for transillumination by interrogating light and the detector ends identified and discretely addressed to a sensor array, the sensor array here illustrated having a corresponding array of condensing lenses for relaying fiber illumination to a detector surface;

Figure 5 illustrates a comparative genomic hybridization process being
25 carried out with two samples for comparison having been previously tagged with differing fluorophores and being added together in a common batch.

Figures 6A and 6B illustrate an expanded detail of the common batch of
30 Figure 5 being transilluminated at the tiered sampling fibers at the sensor end of the array for the excitation of fluorophores attached to the binding partners without undue direct illumination of the fibers themselves.

Figures 7A and 7B illustrate a detector that may be used in conjunction with an optical fiber array or with any other array of light sources (*e.g.* an array of hybridized fluorescent probes).

5

DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is a marked improvement in fiber optic biosensors, methods for fabricating biosensors, and methods for performing qualitative and quantitative measurements of biological molecules using a unique fiber optic biosensor. In particular, the present invention provides for a novel method of construction of a biosensor comprising a high-density array of biological binding partners.

The biosensors of the present invention generally comprise a bundle of coalligned optical fibers. Each individual optical fiber or group of fibers within the biosensor bears a single species of biological binding partner. As used herein biological binding partners are molecules that specifically recognize and bind other molecules thereby forming a binding complex. Typical binding complexes include, but are not limited to, antibody-antigen, lectin-carbohydrate, nucleic acid-nucleic acid, biotin-avidin, receptor-receptor ligand, etc.

The terms "specifically recognize and bind" refers to the binding of a biological binding partner to a particular molecule and to no other molecule to which the biological binding partner is normally exposed. In the case of nucleic acids, specific binding is by hybridization and the terms "specific hybridization" or "specifically hybridizes with" refers to hybridization in which a probe nucleic acid binds substantially to target nucleic acid and does not bind substantially to other nucleic acids present in the biosensor under defined stringency conditions. One of skill will recognize that relaxing the stringency of the hybridizing conditions will allow sequence mismatches to be tolerated. The degree of mismatch tolerated can be controlled by suitable adjustment of the hybridization conditions.

The term "species", as used herein, refers to a biological binding partner capable of specifically binding a particular target molecule. Thus, for example, biological binding partners may both be nucleic acids, but if they have different nucleotide sequences, so that they specifically hybridize to different molecules, they are

considered different species. Similarly, two antibodies specific for different epitopes are considered different species.

In a preferred embodiment the biosensor bears two or more different species of biological binding partner. The use of two or more species of binding partner permits the simultaneous detection of two or more analytes in a test sample with the number of detectable analytes limited only by the number of different biological binding partners present on the biosensor. The biosensor may optionally include additional optical fibers lacking biological binding partners. These additional fibers may bear moieties for the detection of various physical parameters of the test sample, such as temperature or pH, or alternatively may lack any moiety and simply serve as an optical conduit for visualization thereby serving as an endoscope for guiding the insertion of the biosensor probe in various *in vivo* applications.

A biosensor bearing a plurality biological binding partners permits the simultaneous assay of a multiplicity of analytes in a sample. In addition, the measurement of binding of a single analyte to a number of different species of biological binding partners provides a control for non-specific binding. A comparison of the degree of binding of different analytes in a test sample permits evaluation of the relative increase or decrease of the different analytes. Finally, because of the small cross-sectional area of optical fibers, the bundling together into an optical array a number of optical fibers, each bearing a different biological binding partner, provides an effective mechanism for the fabrication of high density arrays of biological binding partners for suitable for a wide variety of *in vivo* and *in vitro* assays.

I. Organization of the Biosensor.

The unique fiber optic biosensor of the present invention, its organization, its construction and its component parts are illustrated by Figures 1-6 respectively. Each discrete fiber optic biosensor is comprised of a plurality of fiber optic strands disposed coaxially along their lengths to form a single, discrete construction. The biosensor thus comprises an optical fiber array, the smallest common repeating unit within which is a single fiber optical strand.

A preferred fiber optical biosensor is illustrated by Figure 4. As seen therein an individual fiber optical strand comprises a single optical fiber having a rod-like shaft and two fiber ends designated a sensor end and a transmission end each

of which provides a substantially planar end surface. The optical fiber strand 10 is typically composed of glass or plastic and is a flexible rod able to convey light energy introduced at either of its ends 11, 12. Such optical fibers 10 are conventionally known and commercially available. Alternatively, the user may himself prepare optical fibers in accordance with the conventional practices and techniques reported by the scientific and industrial literature. Accordingly, the optical fiber 10 is deemed to be conventionally known and available as such.

It will be appreciated that Figures 1-6 are illustrations in which the features have been purposely magnified and exaggerated beyond their normal scale in order to provide both clarity and visualization of extreme detail. Typically, the conventional optical fiber has a cross section diameter of 5-500 micrometers and is routinely employed in lengths ranging between centimeters (*e.g.* in the laboratory) to kilometers (*e.g.* in field telecommunications). Typically, however, when utilized in a biosensor, the optical fibers will preferably range in length from centimeters to about a meter.

Although the optical fiber 10 is illustrated via Figures 1-4 as a cylindrical extended rod having substantially circular end surfaces, there is no requirement or demand that this specific configuration be maintained. To the contrary, the optical fiber may be polygonal or asymmetrically shaped along its length, provide special patterns and shapes at the sensor end or transmission end and need not present an end surface that is substantially planar. Nevertheless, in a preferred embodiment, the optical fiber is substantially cylindrical.

Each optical fiber 10 may be individually clad axially along its length. The cladding may be any material which has a lower refractive index and prevents the transmission of light energy photons from the optical fiber 10 to the external environment. The cladding may thus be composed of a variety of different chemical formulations including various glasses, silicones, plastics, cloths, platings and shielding matter of diverse chemical composition and formulation. Methods of cladding including deposition, extrusion, painting and covering are scientifically and industrially available and any of these known processes may be chosen to meet the requirements and convenience of the user.

The user has a variety of choices at his discretion regarding the configuration of the sensor end 11 of the optical fiber 10. As indicated above, the sensor end 11 may present a surface that is substantially planar and smooth. Alternatively the sensor end 11 may provide an end surface which is essentially convex or concave.

5 It will be appreciated that the range and variety of dimensional and configurational variation of the optical fiber 10 is limited only by the user's ability to subsequently dispose and immobilize a biological binding partner on the intended sensor end 11 of the strand. The use of concave or convex sensor ends 11 will provide greater surface area upon which to immobilize a biological binding partner thereby increasing efficiency (the signal to noise ratio per optical fiber) of the biosensor.

10 While the single repeating component of the fiber optic biosensor is the individual optical fiber 10, it is the aggregation of a plurality of such fibers to form a discrete optical fiber array 14 that permits the simultaneous detection of a multiplicity of analytes. When the optical fibers are aggregated to form a discrete optical fiber array 14, the colligned sensor ends 11 of the fibers are aggregated to form a sensor face 13.

15 A typical biosensor is illustrated in Figure 4 and Figures 6A and 6B in which the sensor face 13 appears in exaggerated, highly simplified views without regard to scale. The optical fiber array 14 comprises a unitary rod-like collective body forming a sensor face 13 and a and a transmission face 15.

20 In practice, it is estimated that there are typically 1000-3000 fiber optical strands in a conventional imaging fiber of 0.5 mm diameter and nearly 1 million strands per square millimeter. The total number of individual fiber optic strands forming the optical fiber array 14 of the present invention will be approximately as great; the total number varying with the cross-sectional diameter of each optical fiber, the pattern of packing of the individual optical fibers in the collective body, and the thickness of cladding material, when employed. It will be appreciated that a 1 square millimeter biosensor, containing nearly 1 million strands in which groups of about 33 optical fibers are each labeled with a different species of biological binding partner will produce a sensor face 13 comprising approximately 30,000 different species of biological binding partner in 1 square millimeter. As explained above, such a sensor could provide nucleic acid biological binding partners covering the entire human genome at 10 megabase intervals.

25

30

5 The sensor face 13 need not be arranged as a planar surface. Rather, the individual optical fibers may be "tiered" so as to protrude from the optical array varying distances. This will maximize the exposure of each optical fiber sensor end 11 both to the sample fluid and to a transilluminating light source 19 as shown in Figures 6A and 6B.

10 In a preferred embodiment, the sensor ends 11 of the optical fibers comprising the optical fiber array 14 will be bundled together in a random or haphazard pattern to form the sensor face 13. Alternatively, the placement of the sensor ends 11 may be highly ordered with the sensor end of each fiber occupying a specific predetermined location in the sensor face 13. As indicated above, the sensor ends 11 of the optical fibers 10 forming the sensor face 13 or the optical fiber array 14 have attached a biological binding partner.

15 Each optical fiber or group of fibers comprising the optical fiber array 14 may bear a different species of biological binding molecule. Although the use of a single species of biological binding partner per optical fiber or group of fibers is preferred, alternatively, each optical fiber or group of fibers may bear a multiplicity of biological binding partners as long as that multiplicity differs from the biological binding partners or multiplicity of biological binding partners present on other fibers or groups of fibers comprising the optical fiber array 14. The fibers bearing like species of binding partner may be physically grouped together thereby producing distinct regions of the sensor face 13 characterized by the presence of a particular biological binding partner or alternatively the fibers bearing different binding partners may be intermingled, the sensor face 13 presenting a relatively uniform or haphazard or random distribution of species of biological binding partners.

25 The transmission face 15 of the optical array may present a substantially planar optical array lacking any further attachments. However, in a preferred embodiment, the transmission face 15 will be permanently or removeably attached to a detector 20, as illustrated in Figure 4. The detector may comprise one or more lenses for focusing and enhancement of an optical signal transmitted along the optical fibers comprising the optical fiber array 14. The detector may additionally comprise a device for transforming the optical signal into a digital or analog electrical signal. Preferred detectors include phototubes (photomultipliers) or charge coupled devices (CCDs). A

single photomultiplier or CCD element may be arranged to measure the aggregate signal provided by the entire transmission face 15 of the biosensor. Alternatively, a CCD (or other) camera may be focused at the transmission face of the biosensor to simultaneously read signals from all of the optical fibers while permitting individual evaluation of the signal from each fiber or group of fibers. In another embodiment, multiple CCD elements or phototubes are used to each detect a signal representing binding of a single species of biological binding partner present at the sensor face 13 of the biosensor. Thus the detector is preferably arranged to read the signal from single optical fibers 10 or from groups of optical fibers where all of the optical fibers 10 in a group bear the same species of biological binding partner.

In addition to detecting optical signals from a fiber optic array, the detector 20, may be generally used to amplify and detect optical signals from any array of light sources. Thus, for example, the array of light sources may be an array of fluorescent spots as due to hybridization of fluorescently labeled probes hybridized to arrays of target nucleic acids. Similarly, the array may be of fluorescently labeled antibodies bound to an array of proteins to which the antibodies bind, or conversely fluorescently labeled proteins bound to an array of antibodies.

In a preferred embodiment suitable for such applications, illustrated in Figures 7A and 7B, the detector 20 may comprise a compound objective lens 31 that consists of an array of single lenses 32. The single lenses are spaced so that each lens is focused on a location 34 in the array where fluorescence is to be measured. The detector may optionally include a beam splitter 35 a second lens 36 an optical filter 37 and a detection device such as a camera 38. The beam splitter is then used to direct an excitation illumination 39 upon the array of light sources. The resulting fluorescence at each spot is then focused through the compound objective lens 31 optionally focused by a second lens, optionally filtered by an optical filter and then detected either visually or by a detection means such as a camera.

The compound objective may be cast, pressed, etched, or ground out of glass, plastic, quartz, or other materials well known as suitable for lens manufacture. The compound lens may be formed as a single piece, or alternatively may be assembled by attaching together simple lenses to form a compound objective.

II. Fabrication of the Biosensor

Figures 1-4 illustrate a method of fabrication of a biosensor comprising a plurality of optical fibers bearing biological binding partners. In general the method involves providing a plurality of optical fibers with each fiber having a sensor end and a transmission end with a particular species of biological binding partner attached to the sensor end of each fiber. Fibers with differing binding partners are combined to form an optical fiber array wherein said fibers have commonly aligned sensor ends for simultaneous assay of a sample. The transmission ends of the combined discrete fibers are addressed for interrogation to produce the fiber optic sensor.

Figure 1, illustrates a particularly preferred embodiment that details one method of providing the optical fibers with attached biological binding partners. A plurality of optical fibers 10 are provided, each fiber having a sensor end 11 and a transmission end 12. The fibers are arranged together to form a plurality of fiber groups or bundles 16, as shown in Figure 2, with the fibers in each bundle disposed coaxially alongside each other with the sensor ends 11 of each fiber commonly aligned at the same end of the bundle. The fibers comprising each bundle may be optionally marked 17 to permit their identification when subsequently removed from the bundle.

As shown in Figure 2, each bundle of fibers is separately treated to attach a particular species of biological binding partner 18 to the sensor ends 11 of the optical fibers comprising the particular bundle. Many methods for immobilizing biological binding partners 18 on a variety of solid surfaces are known in the art. In general, the desired component may be covalently bound or noncovalently attached through nonspecific binding.

In preparing the sensor end 11 for attachment of the binding partner, a plurality of different materials may be employed, particularly as laminates, to obtain various properties. For example, proteins (*e.g.*, bovine serum albumin) or mixtures of macromolecules (*e.g.*, Denhardt's solution) can be employed to avoid non-specific binding, simplify covalent conjugation, enhance signal detection or the like.

If covalent bonding between a biological binding partner and the surface of the sensor end 11 is desired, the surface will usually be polyfunctional or be capable of being polyfunctionalized. Functional groups which may be present on the surface and

used for linking can include carboxylic acids, aldehydes, amino groups, cyano groups, ethylenic groups, hydroxyl groups, mercapto groups and the like.

Covalent linkage of the binding partner to the sensor end may be direct or through a covalent linker. Generally linkers are either hetero- or homo-bifunctional molecules that contain two or more reactive sites that may each form a covalent bond with the respective binding partner. Linkers suitable for joining biological binding partners are well known to those of skill in the art. For example, biological binding partners may be joined by a peptide linker, by a straight or branched chain carbon chain linker, or by a heterocyclic carbon. Heterobifunctional cross linking reagents such as active esters of N-ethylmaleimide have been widely used. See, for example, Lerner *et al. Proc. Nat. Acad. Sci. (USA)*, 78: 3403-3407 (1981) and Kitagawa *et al. J. Biochem.*, 79: 233-236 (1976), which are incorporated herein by reference.

The manner of linking a wide variety of compounds to various surfaces is well known and is amply illustrated in the literature. Proteins, for example, may be joined to linkers or to functional groups on the sensor end by coupling through their amino or carboxyl termini, or through side groups of various constituent amino acids. Thus, coupling through a disulfide linkage to a cysteine is common.

Similarly, methods for immobilizing nucleic acids by introduction of various functional groups to the molecules is known (see, e.g., Bischoff *et al., Anal. Biochem.* 164:336-344 (1987); Kremsky *et al., Nuc. Acids Res.* 15:2891-2910 (1987) which are incorporated herein by reference). Modified nucleotides can be placed on the target using PCR primers containing the modified nucleotide, or by enzymatic end labeling with modified nucleotides.

Preferred methods of immobilizing the nucleic acids and other biomolecules on solid surfaces involve the use of a matrix solution comprising the nucleic acid of interest and an organic or inorganic matrix polymer. Typically, the matrix solution is a monophasic solution comprising both the matrix polymer and the nucleic acid or other biomolecule. In some embodiments, the matrix solution is prepared by mixing the matrix polymer in an appropriate solvent and an aqueous solution of the biomolecule. Exemplary solvents for the matrix polymer useful for this purpose include organic polar solvents such as DMSO, DMF and tetramethylene sulfone, as well as acetonitrile/water solutions, and Bligh and Dyer monophasic solutions.

Alternatively, a diphasic solution comprising a concentrated aqueous solution of the desired nucleic acid or other biomolecule and the matrix polymer in an organic nonpolar solvent such as xylene, toluene, or chloroform can be used. In these embodiments, the diphasic solution must be sonicated or otherwise emulsified to ensure contact between the matrix polymer and the nucleic acid.

A wide variety of organic and inorganic polymers, both natural and synthetic may be employed as the matrix polymer material in the solution. Illustrative polymers which are preferably of low fluorescence, include polyethylene, polypropylene, poly(4-methylbutene), polystyrene, polymethacrylate, poly(ethylene terephthalate), rayon, nylon, poly(vinyl butyrate), polyvinylidene difluoride (PVDF), silicones, polyformaldehyde, cellulose, cellulose acetate, nitrocellulose, and the like.

The matrix solutions of the invention can be used for attachment of nucleic acids and other biopolymers to any solid surface commonly used as a solid surface in nucleic acid hybridization, immunoassays and the like. Exemplary solid surfaces include glass (*e.g.*, optic fibers, slides, and beads), plastics, quartz, and the like.

A particularly preferred method of attaching biological molecules such as nucleic acids to the sensor end of an optic fiber or other solid surface is by mixing a solution of nitrocellulose in DMSO with the biological molecule or with a highly concentrated aqueous solution of molecule. The resulting matrix solution is spotted on the sensor end of the fiber and dried. The ratio of nitrocellulose to biological molecule is preferably adjusted to ensure that the biological molecule is capable of specifically binding with its binding partner (*e.g.*, a complementary nucleic acid) when attached to the surface. In the case of nucleic acids, the ratio of matrix polymer (*e.g.*, nitrocellulose) to nucleic acid is typically between about 1:10 and about 2:1 by weight, usually between about 1.5:10 to about 1:1 by weight.

An exemplary protocol is as follows. A stock solution consisting of about 2 g of nitrocellulose dissolved in 50 ml DMSO is diluted about 100:1 with DMSO. The diluted solution is then mixed with an appropriate amount of nucleic acid such that the final ratio of nitrocellulose to nucleic acid is in the range noted above. For instance, 4 μ l of the diluted DMSO solution (comprising 1.6 μ g nitrocellulose) can be mixed with 10 μ g of DNA. Alternatively, the DMSO solution can be mixed with a concentrated aqueous solution of the DNA to achieve the desired ratio. The nucleic acid need not be

labelled or be absolutely pure and the aqueous solution may contain proteins such as restriction enzymes. The matrix solution containing the nitrocellulose and the nucleic acid is heated to denature the nucleic acid, if required, and applied to a clean, acid washed surface. The spots are then heated for about 0 to about 60 minutes at about 70°C to dry the solution.

Referring to Figure 3, after the biological binding partners 18 are attached to the sensor faces 11 of the optical fibers 10 comprising each bundle, individual fibers, or groups of fibers, are separated from each bundle. In Figure 3, only four fiber bundles $F_1 - F_4$ are illustrated. In the process of being separated from each of the respective fiber bundles $F_1 - F_4$ are individual fibers $10_1 - 10_4$. These respective fibers are being regrouped into optical fiber array 14.

The individual fibers or groups of fibers, may be marked prior to separation from the original bundle to facilitate identification of the binding partner bound to a particular fiber or group during later assembly steps. The separated fibers, or groups of fibers, are recombined with fibers or groups of fibers, separated from different bundles to form an optical fiber array 14 comprising a plurality of fibers or groups of fibers where each fiber or group of fibers bears a different species of biological binding partner.

Figure 4 illustrates that members of the optical fiber array 14 are oriented such that the sensor ends 11 of all of the constituent optical fibers 10 are commonly aligned at the same end of the optical fiber array 14 thereby forming a sensor face 13. The fibers may be arranged in a substantially planar configuration or tiered, as illustrated in Figures 6A and 6B.

The fibers may be bundled at the sensor face 13 in a substantially random or haphazard manner with the relative location of a the sensor end 11 of a particular fiber within the sensor face 13 being determined by chance. Alternatively, the fibers may be positioned within the fiber array in a highly ordered manner such that the location of any particular optical fiber 10 in the sensor face 13 is predetermined.

The transmission ends 12 of the optical fibers comprising the optical fiber array 14 are addressed to permit interrogation and detection of binding events to the biological binding partners attached to the sensor face 13. Addressing is accomplished by any of a number of means well known to those of skill in the art. In a preferred

embodiment, the transmission ends 12 of individual optical fibers, or groups of optical fibers all bearing the same species of biological binding partner, are spatially addressed. This comprises localizing the optical fibers or bundles of optical fibers at fixed locations relative to the other optical fibers or bundles of optical fibers comprising the optical fiber array 14, see *e.g.* Figure 4. Most typically this may be accomplished by attaching the fiber array to a fiber optic connector and ferrule (*e.g.* see AMP, Inc. Harrisburg, PA).

Alternatively, the transmission ends 12, may be addressed by attaching the transmission end of each optical fiber 10 or bundle of optical fibers bearing a particular biological binding partner to an individual detector. Each detector is subsequently known to be associated with a particular biological binding partner and there is no need to preserve a fixed spatial relationship between any of the transmission ends 12.

Detection of a signal from the biosensor (optical array) may be accomplished by visual inspection of the transmission face 15 of the optical fiber array 14 or by the use of one or more detectors 20. As indicated above, the transmission face may be permanently or removably attached to a single optical lens or system of multiple optical lenses. The lens or lenses may be arranged to focus an optical signal from the entire transmission face 15 or from selected subregions of the transmission face. In a preferred embodiment, lenses will be arranged to each focus an optical signal from the portion of the transmission face 15 corresponding to a single biological binding partner. In the extreme case, the signal for each optical fiber comprising the optical fiber array 14 will be individually focused.

Again with a lens or lens system present, the signal may be simply detected visually. However, in a preferred embodiment, the use of detectors is contemplated. Preferred detectors are devices that convert an optical signal into a digital or analog electrical signal. Typically detectors are of two general types: phototubes and charge coupled devices (CCDs). A single photomultiplier or CCD element may be utilized to measure the aggregate signal provided by the entire transmission face 15 of the biosensor. More preferably, however, multiple CCD elements or phototubes are used to each detect a signal representing binding of a single species of biological binding partner present at the sensor face 13 of the optical fiber array 14.

The detector system may be employed with a computerized data acquisition system and analytical program. In this embodiment, providing a fully

5

II. Methods of Use

10

15

25

30

binding complex may be used as the biological binding member attached to the sensor end 11 of the optical fibers comprising the biosensor. Thus, for example, where it is desired to detect an antibody in a sample, the corresponding antigen may be attached to the sensor end. Conversely, where it is desired to detect the antigen in the sample, the antibody may be attached to the sensor end.

The selection of binding partners for a particular assay is well known to those of skill in the art. Typically, where proteins are to be detected, antibodies are most preferred as the biological binding partner. Where enzymatic substrates are to be detected, enzymes are preferred biological binding partners, and where nucleic acids are to be detected, nucleic acid binding partners are most preferred. Thus, for example, fiber optic biosensors have been described that utilize enzymes such as xanthine oxidase and peroxidase to detect hypoxanthine and xanthine (Hlavay *et al.*, *Biosensors and Bioelectronics*, 9(3): 189-195 (1994), that use alkaline phosphatase to detect organophosphorous-based pesticides (Gao *et al.* *Proceedings -- Lasers and Electro-Optics Society, Annula Meeting*, 8(4): abstract 20782 (1994), and that use antibodies or DNA binding proteins (Anderson, *et al.*, *Fiber Optic Medical and Fluorescent Sensors and Applications*, *Proc. S.P.I.E.* 1648: 39-43 (1992).

Of course the biosensor may be designed to simultaneously detect several different classes of analyte. Thus the sensor may bear a combination of two or more different classes of biological binding partner. The sensor face 13 will bear one or more binding partners selected, for example, from the group consisting of nucleic acids, proteins, antibodies, carbohydrates, biotin, avidin, and lectins.

In the simplest application, the biosensor of the present invention may be utilized to detect a single analyte in a test sample. The test sample may be *in vivo*, in culture, or *in vitro*. The assay may register simple presence or absence of the analyte or may quantify the amount of analyte present in the sample.

The assay may be run in either a direct or a competitive format. In a direct format, the amount of analyte is determined directly measuring the analyte bound to the biological binding partner. In a competitive format, a known analyte is present in the sample and the test analyte is detected by its ability to compete the known analyte from the biological binding partners present on the sensor face 13.

In a preferred method of use, the optical fibers 10 comprising the optical fiber array 14 conduct an optical signal indicative of the binding between a biological binding partner on the sensor face 11 and the analyte in the sample. The optical signal may be produced by a number of means known to those of skill in the art. Typically the optical signal is generated by a fluorescent, luminescent, or colorimetric label present at the sensor end 11 of the optical fiber 10. Typically the concentration of label at the sensor end of the optical fiber is a function of the concentration of analyte that specifically binds to the biological binding partner present on that sensor end.

Methods of providing a label whose concentration is a function of the amount of an analyte specifically associated with a biological binding partner are well known to those of skill in the art. In the simplest approach, the analyte itself is labeled. Binding of the analyte to the binding partner then brings the label into proximity with the sensor end 11 to which the binding partner is attached. Alternatively, a labeled "blocking" analyte may be provided in the test sample or pre-bound to the biosensor. Displacement of the labeled "blocking" analyte by the unlabeled test analyte in the sample produces a reduction of label bound to the sensor end where the reduction is proportional to the concentration of unlabeled analyte in the test sample.

Other approaches may use a second biological binding partner that itself is labeled. The first biological binding partner attached to the sensor end binds and thereby immobilizes the analyte. The second, labelled binding partner then binds to the analyte immobilized on the sensor end thereby bringing the label in close proximity to the sensor end where it may be detected.

Luminescent labels are detected by measuring the light produced by the label and conducted along the optical fiber. Luminescent labels typically require no external illumination.

In contrast colorimetric or fluorescent labels typically require a light source. Colorimetric labels typically produce an increase in optical absorbance and/or a change in the absorption spectrum of the solution. Colorimetric labels are measured by comparing the change in absorption spectrum or total absorbance of light produced by a fixed light source. In the present invention, the change in light absorbance or absorption spectrum is preferably detected through the optical fibers comprising the biosensor. The change in absorbance, or absorption spectrum, may be measured as a change in

illumination from an absolutely calibrated light source, or alternatively may be made relative to a second "reference light source". The light source may be external to the biosensor or may be provided as an integral component. In one embodiment, some of the constituent optical fibers will conduct light from the signal and/or reference source to
5 the sensor face. For maximum sensitivity the light used to measure absorbance, or absorption spectrum, changes will be directed directly at the sensor face of the biosensor.

Fluorescent labels produce light in response to excitation by a light source. The emitted light, characteristically of a different (lower) wavelength than the excitation illumination, is detected through the optical fiber to which the fluorescent label has
10 become bound.

The excitation illumination may be provided by an integral component of the biosensor or by a separate light source according to a number of methods well known to those of skill in the art. Evanescent wave systems involve introducing a light beam at the transmission end 12 of the optical fiber. This light beam is conducted along the fiber
15 until it reaches the sensor end 11 of the fiber where it generates in the test solution an electromagnetic waveform known as the evanescent wave component. The evanescent wave component may be sufficient to excite a fluorophore and produce a fluorescent signal. (See, for example U.S. Pat. No. 4,447,546 and U.S. Pat. No. 4,909,990 which are incorporated herein by reference).

20 In another embodiment, the excitation illumination is provided external to the biosensor. It is particularly preferred that the illumination be provided as a "transillumination" normal to the sensor ends 11 of the optical fibers (see, *e.g.* Figure 4). This provides an increased signal to noise ratio as, in this configuration, most of the excitation illumination will not be conducted along the optical fibers. The individual
25 optical fibers 10 comprising the biosensor may be tiered, for example, as shown in Figures 6A and 6B, to prevent individual fibers from shadowing each other when transilluminated.

To optimize a given assay format one of skill can determine sensitivity of fluorescence detection for different combinations of optical fiber, sensor face
30 configuration, fluorochrome, excitation and emission bands and the like. The sensitivity for detection of analyte by various optical fiber array configurations can be readily determined by, for example, using the biosensor to measure a dilution series of

fluorescently labeled analytes. The sensitivity, linearity, and dynamic range achievable from the various combinations of fluorochrome and biosensor can thus be determined. Serial dilutions of pairs of fluorochromes in known relative proportions can also be analyzed to determine the accuracy with which fluorescence ratio measurements reflect actual fluorochrome ratios over the dynamic range permitted by the detectors and biosensor.

Use in Comparative Genomic Hybridization

In a particularly preferred embodiment, the biosensor of the present invention will be used in a Comparative Genomic Hybridization (CGH) assay. Comparative genomic hybridization (CGH) is a recent approach used to detect the presence and identify the chromosomal location of amplified or deleted nucleotide sequences. (See, Kallioniemi *et al.*, *Science* 258: 818-821 (1992), WO 93/18186, and copending application U.S.S.N. 08/353,018, filed on December 9, 1994, which are incorporated herein by reference).

In the traditional implementation of CGH, genomic DNA is isolated from normal reference cells, as well as from test cells (*e.g.*, tumor cells). The two nucleic acids (DNA) are labelled with different labels and then hybridized *in situ* to metaphase chromosomes of a reference cell. The repetitive sequences in both the reference and test DNAs may be removed or their hybridization capacity may be reduced by some means such as an unlabeled blocking nucleic acid (*e.g.* Cot-1). Chromosomal regions in the test cells which are at increased or decreased copy number can be quickly identified by detecting regions where the ratio of signal from the two DNAs is altered. For example, those regions that have been decreased in copy number in the test cells will show relatively lower signal from the test DNA than the reference compared to other regions of the genome. Regions that have been increased in copy number in the test cells will show relatively higher signal from the test DNA.

In one embodiment, the present invention provides a CGH assay in which the biosensor of the present invention replaces the metaphase chromosome used as the hybridization target in traditional CGH. Instead, the biological binding partners present on the biosensor are nucleic acid sequences selected from different regions of the genome. The biosensor itself becomes a sort of "glass chromosome" where hybridization

of a nucleic acid to a particular binding partner is informationally equivalent to hybridization of that nucleic acid to the region on a metaphase chromosome from which the biological binding partner is derived. In addition, nucleic acid binding partners not normally contained in the genome, for example virus nucleic acids, can be employed.

5 More particularly, in a CGH assay, the biosensor may be utilized in methods for quantitatively comparing copy numbers of at least two nucleic acid sequences in a first collection of nucleic acid molecules relative to the copy numbers of those same sequences in a second collection, as illustrated in Figure 5. The method comprises labeling the nucleic acid molecules in the first collection 25 and the nucleic
10 acid molecules in the second collection 26 with first and second labels, respectively thereby forming at least two collections of nucleic acid probes. The first and second labels should be distinguishable from each other.

As used herein, the term "probe" is thus defined as a collection of nucleic acid molecules (either RNA or DNA) capable of binding to a target nucleic acid of
15 complementary sequence through one or more types of chemical bonds, usually through hydrogen bond formation. The probes are preferably directly or indirectly labelled as described below. They are typically of high complexity, for instance, being prepared from total genomic DNA or mRNA isolated from a cell or cell population.

The probes 30 thus formed are contacted, either simultaneously or serially,
20 to a plurality of target nucleic acids, present on the sensor face 13 of the biosensor of array 14 under conditions such that nucleic acid hybridization to the target nucleic acids can occur. Here a transilluminating light source 19 is utilized. After contacting the probes to the target nucleic acids the amount of binding of each probe, and ratio of the binding of the probes is determined for each species of target nucleic acid. Typically the
25 greater the ratio of the binding to a target nucleic acid, the greater the copy number ratio of sequences in the two probes that bind to nucleic acid. Thus comparison of the ratios of bound labels among target nucleic acid sequences permits comparison of copy number ratios of different sequences in the probes.

In a preferred embodiment, the sequence complexity of each target nucleic
30 acid in the biosensor is much less than the sequence complexity of the first and second collections of labeled nucleic acids. The term "complexity" is used here according to standard meaning of this term as established by Britten *et al. Methods of Enzymol.*

29:363 (1974). *See, also* Cantor and Schimmel *Biophysical Chemistry: Part III* at 1228-1230 for further explanation of nucleic acid complexity.

The methods are typically carried out using techniques suitable for fluorescence in situ hybridization. Thus, the first and second labels are usually fluorescent labels.

To inhibit hybridization of repetitive sequences in the probes to the target nucleic acids, unlabeled blocking nucleic acids (e.g., Cot-1 DNA) can be mixed with the probes. Thus, the invention focuses on the analysis of the non-repetitive sequences in a genome. However, use of repetitive sequences as targets on the biosensor and omitting the blocking nucleic acids would permit relative copy number determinations to be made for repetitive sequences.

In a typical embodiment, one collection of probe nucleic acids is prepared from a test cell, cell population, or tissue under study; and the second collection of probe nucleic acids is prepared from a reference cell, cell population, or tissue. Reference cells can be normal non-diseased cells, or they can be from a sample of diseased tissue that serves as a standard for other aspects of the disease. For example, if the reference probe is genomic DNA isolated from normal cells, then the copy number of each sequence in that probe relative to the others is known (e.g., two copies of each autosomal sequence, and one or two copies of each sex chromosomal sequence depending on gender). Comparison of this to a test probe permits detection in variations from normal. Alternatively the reference probe may be prepared from genomic DNA from a primary tumor which may contain substantial variations in copy number among its different sequences, and the test probe may be prepared from genomic DNA of metastatic cells from that tumor, so that the comparison shows the differences between the primary tumor and its metastasis. Further, both probes may be prepared from normal cells. For example comparison of mRNA populations between normal cells of different tissues permits detection of differential gene expression that is a critical feature of tissue differentiation. Thus in general the terms test and reference are used for convenience to distinguish the two probes, but they do not imply other characteristics of the nucleic acids they contain.

Target nucleic acids

The target nucleic acids comprising the biological binding partners attached to the sensor ends 11 of the optical fibers 10 and the probes may be, for example, RNA, DNA, or cDNA. The nucleic acids may be from any organism. The nucleic acids may be genomic sequences which correspond to specific regions of a chromosome or may be expressed sequences, such as cDNA or mRNA. Usually the nucleic acid in the target sequences and the probes are from the same species.

The "target nucleic acids" comprising biological binding partners typically have their origin in a defined region of the genome (for example a clone or several contiguous clones from a genomic library), or correspond to a functional genetic unit, which may or may not be complete (for example a full or partial cDNA). The target nucleic acids can also comprise inter-*Alu* or Degenerate Oligonucleotide Primer PCR products derived from such clones. If gene expression is being analyzed, a target element can comprise a full or partial cDNA.

The target nucleic acids may, for example, contain specific genes or, be from a chromosomal region suspected of being present at increased or decreased copy number in cells of interest, *e.g.*, tumor cells. The target nucleic acid may also be an mRNA, or cDNA derived from such mRNA, suspected of being transcribed at abnormal levels.

Alternatively, target nucleic acids may comprise nucleic acids of unknown significance or location. The array of such target nucleic acids comprising the sensor face 13 of a biosensor of the present invention could represent nucleic acids derived from locations that sample, either continuously or at discrete points, any desired portion of a genome, including, but not limited to, an entire genome, a single chromosome, or a portion of a chromosome. The number of target elements and the complexity of the nucleic acids in each would determine the density of sampling. For example an biosensor bearing 300 different species of target nucleic acid (biological binding partners), each target nucleic acid being DNA from a different genomic clone, could sample the entire human genome at 10 megabase intervals. An array of 30,000 elements, each containing 100kb of genomic DNA could give complete coverage of the human genome.

Similarly, an array of target nucleic acids comprising nucleic acids from anonymous cDNA clones would permit identification of those that might be differentially expressed in some cells of interest, thereby focusing attention on study of these genes.

5 In some embodiments, previously mapped clones from a particular chromosomal region of interest are used as targets. Such clones are becoming available as a result of rapid progress of the worldwide initiative in genomics.

Mapped clones can be prepared from libraries constructed from single chromosomes, multiple chromosomes, or from a segment of a chromosome. Standard techniques are used to clone suitably sized fragments in vectors such as cosmids, yeast
10 artificial chromosomes (YACs), bacterial artificial chromosomes (BACs) and P1 phage.

While it is possible to generate clone libraries, as described above, libraries spanning entire chromosomes are also available commercially. For instance, chromosome-specific libraries from the human and other genomes are available from Clontech (South San Francisco, CA) or from The American Type Culture Collection
15 (see, *ATCC/NIH Repository of Catalogue of Human and Mouse DNA Probes and Libraries*, 7th ed. 1993).

If necessary, clones described above may be genetically or physically mapped. For instance, FISH and digital image analysis can be used to identify and map the locations on a chromosome to which specific cosmid inserts hybridize. This method
20 is described, for instance, in Lichter *et al.*, *Science*, 247:64-69 (1990). The physically mapped clones can then be used to more finally map a region of interest identified using CGH or other methods.

One of skill will recognize that each target nucleic acids may be selected so that a number of nucleic acids of different length and sequence represent a particular
25 region on a chromosome. Thus, for example, a the sensor face 13 of the biosensor may bear more than one copy of a cloned piece of DNA, and each copy may be broken into fragments of different lengths. One of skill can adjust the length and complexity of the target sequences to provide optimum hybridization and signal production for a given hybridization procedure, and to provide the required resolution among different genes or
30 genomic locations. Typically, the target sequences will have a complexity between about 1 kb and about 1 Mb.

Preparation of probe nucleic acids

As with target nucleic acids (those attached to the fiber optic sensor), a wide variety of nucleic acids can be used as probe nucleic acids in the methods of the present invention. The probes may be comprise, for example, genomic DNA
5 representing the entire genome from a particular organism, tissue or cell type or may comprise a portion of the genome, such as a single chromosome.

To compare expression levels of a particular gene or genes, the probe nucleic acids can be derived from mRNA or cDNA prepared from an organism, tissue, or cell of interest. For instance, test cDNA or mRNA, along with mRNA or cDNA
10 from normal reference cells, can be hybridized to an array of target nucleic acids on the sensor comprising clones from a normalized cDNA library. In addition, probes made from genomic DNA from two cell populations can be hybridized to a target cDNA array to detect those cDNAs that come from regions of variant DNA copy number in the genome.

The methods of the invention are suitable for comparing copy number of particular sequences in any combination of two or more populations of nucleic acids. One of skill will recognize that the particular populations of sample nucleic acids being compared is not critical to the invention. For instance, genomic or cDNA can be compared from two related species. Alternatively, levels of expression of particular
15 genes in two or more tissue or cell types can be compared. As noted above, the methods are particularly useful in the diagnosis of disease.

Standard procedures can be used to isolate nucleic acids (either DNA or mRNA) from appropriate tissues (*see, e.g., Sambrook, et al., Molecular Cloning - A Laboratory Manual*, Cold Spring Harbor Laboratory, Cold Spring Harbor, N.Y. (1985)).
20 Conventional methods for preparation of cDNA from mRNA can also be used.

The particular cells or tissue from which the nucleic acids are isolated will depend upon the particular application. Typically, for detection of abnormalities associated with cancer, genomic DNA is isolated from tumor cells. For prenatal detection of disease, fetal tissue will be used.

If the tissue sample is small, so that a small amount of nucleic acids is available, amplification techniques such as the polymerase chain reaction (PCR) using degenerate primers can be used. For a general description of PCR, *see, PCR Protocols*,
30

Innis *et al.* eds. Academic Press, 1990. In addition, PCR can be used to selectively amplify sequences between high copy repetitive sequences. These methods use primers complementary to highly repetitive interspersed sequences (*e.g.*, *Alu*) to selectively amplify sequences that are between two members of the *Alu* family (*see*, Nelson *et al.*,
5 *Proc. Natl. Acad. Sci. USA* 86:6686 (1989)).

CGH, at the cytogenetic level, facilitates the search for disease genes by identifying regions of differences in copy number between a normal and tumor genome, for example. For instance, CGH studies have been applied to the analysis of copy number variation in breast cancer (*see, e.g.*, Kallioniemi *et al. Proc. Natl. Acad. Sci.*
10 *USA* 91:2156-2160 (1994)).

In CGH, the resolution with which a copy number change can be mapped is on the order of several megabases. With the present invention the resolution is a function of the length of the genomic DNA segments comprising the target nucleic acid sequences and the difference in map position between neighboring clones. Resolution of
15 more than a factor of 10 better than with standard CGH can be achieved with the present invention. This improved localization will facilitate efforts to identify the critical genes involved in a disease, and permit more sensitive detection of abnormalities involving a small region of the genome, such as in microdeletion syndromes.

Labeling nucleic acid probes

As noted above, the nucleic acids which are hybridized to the target
20 nucleic acids are preferably labeled to allow detection of hybridization complexes. The nucleic acid probes used in the hybridization described below may be detectably labeled prior to the hybridization reaction. Alternatively, a detectable label may be selected which binds to the hybridization product. As noted above, the target nucleic acid array
25 is hybridized to two or more probe nucleic acids, either simultaneously or serially. Thus, the probes are each preferably labeled with a separate and distinguishable label.

The particular label or detectable group attached to the probe nucleic acids is selected so as to not significantly interfere with the hybridization of the probe to the target sequence. The detectable group can be any material having a detectable physical
30 or chemical property. Such detectable labels have been well-developed in the field of nucleic acid hybridizations and in general most any label useful in such methods can be applied to the present invention. Thus a label is any composition detectable by

spectroscopic, photochemical, biochemical, immunochemical, electrical, optical or chemical means.

However, preferred labels produce an optical signal. Thus, particularly useful labels in the present invention include fluorescent dyes (*e.g.*, fluorescein isothiocyanate, texas red, rhodamine, and the like) and labels that produce a colorimetric signal such as various enzymes (*e.g.*, horse radish peroxidase, alkaline phosphatase and others commonly used in an ELISA).

The nucleic acids can be indirectly labeled using ligands for which detectable anti-ligands are available. For example, biotinylated nucleic acids can be detected using labeled avidin or streptavidin according to techniques well known in the art. In addition, antigenic or haptenic molecules can be detected using labeled antisera or monoclonal antibodies. For example, N-acetoxy-N-2-acetylaminofluorene-labelled or digoxigenin-labelled probes can be detected using antibodies specifically immunoreactive with these compounds (*e.g.*, FITC-labeled sheep anti-digoxigenin antibody (Boehringer Mannheim)). In addition, labeled antibodies to thymidine-thymidine dimers can be used (Nakane *et al.* *ACTA Histochem. Cytochem.* 20:229 (1987)).

Generally, labels which are detectable in as low a copy number as possible, thereby maximizing the sensitivity of the assay, and yet be detectable above any background signal are preferred. A label is preferably chosen that provides a localized signal, thereby providing spatial resolution of the signal from each target element.

The labels may be coupled to the DNA in a variety of means known to those of skill in the art. In a preferred embodiment the probe will be labeled using nick translation or random primer extension (Rigby, *et al.* *J. Mol. Biol.*, 113: 237 (1977) or Sambrook, *et al.*, *Molecular Cloning - A Laboratory Manual*, Cold Spring Harbor Laboratory, Cold Spring Harbor, N.Y. (1985)).

Hybridization of labeled nucleic acids to targets

The copy number of particular nucleic acid sequences in two probes are compared by hybridizing the probes to one or more target nucleic acid arrays (biosensors). The hybridization signal intensity, and the ratio of intensities, produced by the probes on each of the target elements is determined. Typically the greater the ratio of the signal intensities on a target nucleic acid the greater the copy number ratio of sequences in the two probes that bind to that target sequence. Thus comparison of the

signal intensity ratios among target elements permits comparison of copy number ratios of different sequences in the probes.

Standard hybridization techniques are used to probe a target nucleic acid array. Suitable methods are described in references describing CGH techniques
5 (Kallioniemi *et al.*, *Science* 258: 818-821 (1992) and WO 93/18186). Several guides to general techniques are available, *e.g.*, Tijssen, *Hybridization with Nucleic Acid Probes*, Parts I and II (Elsevier, Amsterdam 1993). For a description of techniques suitable for *in situ* hybridizations *see*, Gall *et al. Meth. Enzymol.*, 21:470-480 (1981) and Angerer *et al.* in *Genetic Engineering: Principles and Methods* Seilow and Hollaender, Eds. Vol 7,
10 pgs 43-65 (plenum Press, New York 1985).

Generally, nucleic acid hybridizations utilizing the biosensors of the present invention comprise the following major steps: (1) prehybridization treatment to increase accessibility of target DNA, and to reduce nonspecific binding; (2) hybridization of the mixture of nucleic acids to the nucleic acid targets on the biosensor; (3)
15 posthybridization washes to remove nucleic acid fragments not bound in the hybridization and (4) detection of the hybridized nucleic acid fragments. The reagent used in each of these steps and their conditions for use vary depending on the particular application.

In some applications it is necessary to block the hybridization capacity of repetitive sequences. A number of methods for removing and/or disabling the
20 hybridization capacity of repetitive sequences are known (*see, e.g.*, WO 93/18186).

For instance, bulk procedures can be used. In many genomes, including the human genome, a major portion of shared repetitive DNA is contained within a few families of highly repeated sequences such as *Alu*. These methods exploit the fact that hybridization rate of complementary sequences increases as their concentration increases.
25 Thus, repetitive sequences, which are generally present at high concentration will become double stranded more rapidly than others following denaturation and incubation under hybridization conditions. The double stranded nucleic acids are then removed and the remainder used in hybridizations. Methods of separating single from double stranded sequences include using hydroxyapatite or immobilized complementary nucleic acids
30 attached to a solid support. Alternatively, the partially hybridized mixture can be used and the double stranded sequences will be unable to hybridize to the target.

Alternatively, unlabeled sequences which are complementary to the sequences whose hybridization capacity is to be inhibited can be added to the hybridization mixture. This method can be used to inhibit hybridization of repetitive sequences as well as other sequences. For instance, "Cot-1" DNA can be used to selectively inhibit hybridization of repetitive sequences in a sample. To prepare Cot-1 DNA, DNA is extracted, sheared, denatured and renatured to a $C_0t \sim 1$ (for description of reassociation kinetics and C_0t values, *see*, Tijssen, *supra* at pp 48-54). Because highly repetitive sequences reanneal more quickly, the resulting hybrids are highly enriched for these sequences. The remaining single stranded (*i.e.*, single copy sequences) is digested with S1 nuclease and the double stranded Cot-1 DNA is purified and used to block hybridization of repetitive sequences in a sample. Although Cot-1 DNA can be prepared as described above, it is also commercially available (BRL). Reassociation to large C_0t values will result in blocking DNA containing repetitive sequences that are present at lower copy number.

Analysis of detectable signals from hybridizations

Standard methods for detection and analysis of signals generated by labeled probes can be used. In particular, the optical signal produced by binding of a labeled probe to a particular binding partner will be carried along the optical fibers 10, to which that binding partner is attached. As indicated above, the optical signal may be visualized directly or transduced into an analog or digital electronic signal by means of a detector 20. To facilitate the display of results and to improve the sensitivity of detecting small differences in fluorescence intensity, a detector and a digital signal analysis system is preferably used. The detector may be equipped with one or more filters to pass the emission wavelengths while filtering out excitation wavelengths thereby increase the signal to noise ratio. The use of filters will also facilitate distinguishing between binding events involving the two, or more, differently labeled probes. Such detector/filter/signal processing systems are well known to those of skill in the art.

WHAT IS CLAIMED IS:

1. A process for attaching a biological binding partner to a solid surface using a matrix polymer, the process comprising the steps:

5 forming a matrix solution comprising the nucleic acid and a matrix polymer;

contacting the matrix solution with the solid surface, thereby attaching the biological binding partner such that it can specifically recognize and bind a second molecule.

10 2. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the step of forming the matrix solution comprises contacting an aqueous solution comprising the biological binding partner with a second solution comprising the matrix polymer.

15 3. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the biological binding partner is a nucleic acid and is attached to the solid surface such that the nucleic acid is capable of specifically hybridizing with a complementary nucleic acid.

20 4. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the solid surface is a glass slide.

25 5. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the solid surface is a sensor end of an optical fiber.

30 6. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the matrix polymer is nitrocellulose.

7. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, wherein:

the second solution comprises nitrocellulose dissolved in DMSO.

5 8. A process for attaching a biological binding partner to a solid surface using a matrix polymer according to claim 1, further comprising the step of drying the matrix solution after contacting the matrix solution with the solid surface.

10 9. A process for constructing a fiber optic bundle for sensing a plurality of biological binding partners within a sample, the process comprising the steps of:

15 providing a plurality of optical fibers with each fiber having a sensor end and a transmission end wherein each fiber has attached to its sensor end a species of biological binding partner, the binding partner being attached to the sensor end of the optical fiber using a matrix polymer, such that the biological binding partner can specifically recognize and bind a second molecule.;

 combining said fibers with differing binding partners to form an optical fiber array wherein said fibers have commonly aligned sensor ends for simultaneous assay of a sample; and,

20 addressing the transmission end of the combined discrete fibers for interrogation to produce the fiber optic sensor for the sample.

 10. The process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

25 the matrix polymer is nitrocellulose.

 11. The process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

30 the biological binding partner is a nucleic acid and is attached to the sensor end such that the nucleic acid is capable of hybridizing to a complementary nucleic acid.

12. The process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein said providing step comprises:

providing a plurality of optical fibers with each fiber having a sensor end
5 and a transmission end;

placing the plurality of optical fibers in a plurality of fiber groups, each fiber group with commonly aligned sensor ends for simultaneous treatment;

providing a plurality of differing batches, each batch comprising a single species of biological binding partner suitable for attachment under treatment to the
10 commonly aligned sensor ends of the optical fibers of a selected group of optical fibers;

placing and treating the commonly aligned sensor ends of differing fiber groups in differing batches with differing biological binding partners to produce a plurality of groups of optical fibers with the sensor ends of the optical fibers of each group having the same species of biological binding partner and the sensor ends of
15 optical fibers of differing groups having differing species of biological binding partners;
and

separating fibers from each group of fibers thereby providing a plurality of optical fibers with each fiber having a sensor end and a transmission end wherein each fiber has attached to its sensor end a species of biological binding partner.
20

13. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

the combining separated fibers with differing binding partners with commonly aligned sensor ends includes randomly gathering the sensor ends.
25

14. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

the combining separated fibers with differing binding partners with commonly aligned sensor ends includes assembling said sensor ends to form a tiered
30 sensor face.

15. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

the combining separated fibers with differing binding partners with commonly aligned sensor ends includes assembling said sensor ends to form a planer sensor face.

16. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

the addressing the transmission end of the recombined discrete fibers for interrogation includes addressing the transmission ends of each of the discrete fibers to an optical array.

17. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

transmission ends of the optical fibers of each group having similar binding partners have similar markings for distinguishing the transmission ends corresponding to binding partners.

18. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 9, wherein:

the providing a plurality of batches of differing binding partners includes batches of nucleic acid binding partners to which nucleic acids in the sample might hybridize.

19. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 18, wherein:

the nucleic binding partners each correspond to specific regions on chromosomes.

20. A process for constructing a fiber optic bundle for sensing a plurality of binding partners within a sample according to claim 18, wherein:

the nucleic binding partners each correspond to expressed sequences.

1/5




FIG. 1.




FIG. 2.

2/5




FIG. 3.




FIG. 4.

3/5




FIG. 5.

4/5




FIG. 6A.




FIG. 6B.

5/5




FIG. 7A.




FIG. 7B.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/01052

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) Please See Extra Sheet.

US CL Please See Extra Sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. 435/5, 6, 91.1, 91.2; 65/409; 422/82.05, 82.06, 82.07, 82.08, 82.09; 436/172; 250/227.23

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Please See Extra Sheet.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ----- Y	US 5,244,636 A (WALT et al) 14 September 1993, see entire document.	1, 2, 5, 8 ----- 3, 4, 6, 7, 9-20
Y	US H1398 A (CAMPBELL) 03 January 1995, see entire document.	1-20
A	US 5,304,492 A (KLINKHAMMER) 19 April 1994, see entire document.	1-20
Y	US 5,082,630 A (PARTIN et al) 21 January 1992, see entire document.	1-20
Y	US 5,166,990 A (RICCITELLI et al) 24 November 1992	14

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T	later documents published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

13 MARCH 1997

Date of mailing of the international search report

13 MAY 1997

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JEREMY FREDMAN

Telephone No. (202) 208-0196

Form PCT/ISA/210 (second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/01052

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,449,625 A (KOBAYASHI et al) 12 September 1995, see entire document.	1-20
A	US 5,260,029 (HOSOI et al) 09 November 1993, see entire document.	1-20
Y	GRAHAM et al. Gene probe assays on a fibre-optic evanescent wave biosensor. Biosensors & Bioelectronics. 1992. Vol. 7. pages 487-493, see entire document.	1-20
Y	BARNARD et al. A fibre-optic chemical sensor with discrete sensing sites. Nature. 26 September 1991. Vol. 353. pages 338-340, see entire document.	1-20
Y	LIPSON et al. Multifiber, multiwavelength, fiber optic fluorescence spectrophotometer. IEEE Trans. Biomed. Engineer. 09 September 1992. Vol. 39. No. 9. pages 886-892, see entire document.	1-20
Y	MCCURLEY et al. An optical biosensor using a fluorescent swelling sensing element. Biosensors & Bioelectronics. 1994. Vol. 9. pages 527-533, see entire document.	1-20
Y	BLUM et al. Luminescence fiber optic biosensor. Anal. Lett. 1988. Vol. 21. No. 5. pages 717-726, see entire document.	1-20
Y	PIUNNO et al. Fiber-optic based DNA sensor for fluorometric nucleic acid determination. August 1995. Anal. Chem. Vol. 67. No. 15. pages 2635-2643, see entire document.	1-20

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/01052

A. CLASSIFICATION OF SUBJECT MATTER:

IPC (6):

C12Q 1/68, 1/70; C12P 19/34; C03B 37/15, G01N 21/01, 21/29, 27/00, 27/30, 21/27, 21/31, 21/76, 21/25

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

435/5, 6, 91.1, 91.2, 65/409; 422/82.05, 82.06, 82.07, 82.08, 82.09; 436/172, 250/227.23

B. FIELDS SEARCHED

Electronic data bases consulted (Name of data base and where practicable terms used):

APS USPAT, MEDLINE, BIOSIS, CAPLUS, WPIDS

search terms: biosensor, sensor, fiber, optic, address, DNA, RNA, nucleic, oligonucleotide, polynucleotide, photolithography, bundle, matrix, support, surface, polymer, nitrocellulose, tiered